

ëstic

Installation Guide

1.

Organize the received panels in alignment with your intended design concept. You may customize the color combinations of your specific set of panels to suit your design.



2.

After finalizing your design, you may start application of double-sided tape to the panels. Ensure that the double-sided tape is applied to the side of the panel you wish to keep concealed



Additionally, a spacer tool is provided in case there is need to add even gaps in your design.

3.

Double-sided tape is to be applied on all corners of the panel to ensure a strong hold. Also ensure that the wall surface is dust-free before the wall panel installation.

4.

Proper measurement and alignment of the panels should be done prior to wall surface attachment. Attach as planned and there you have it!



estic

Cleaning & Care Guide

General Care

Light vacuuming on a regular basis will prevent dust build up. Ensure to only use a soft brush attachment with low suction function.

Periodic dusting may also be required. You may dust with a soft cloth to maintain panel appearance. Avoid severe abrasion on the panel.

Spot Cleaning

Spills, marks and stains should be treated as soon as possible. Blot away any excessive moisture from spills off the material as quickly as possible.

Most marks can be cleaned with mild detergent and warm water solution but avoid using excessive amounts of water or other cleaning agent/liquids. Note that we do not recommend using solvent based cleaners. Ensure panel can dry through adequate ventilation.

Use blotting technique with minimal pressure and avoid excessive rubbing. Note to take extra precaution when cleaning dark coloured panels.

Handling & Storage

When handling panels, be sure your hands are clean and free of any contaminants or oils. Keep dust, dirt and liquids of any kind away from all edges and faces of panels at all times.

Panels must be stored in dry locations/indoors, away from any heating sources. Do not allow water to come into direct contact with the panels. Moisture exposure can cause material to warp, stain or delaminate.

DISCLAIMER: Estic suggests stated cleaning methods in good faith, however, the customer undertakes cleaning treatment at their own risk. Estic will not be responsible for unsatisfactory results arising from the proposed treatments listed herein.

Connect with us:

 info@estic.com.my

 +60 10-265 9960

 No 25-G, Jalan Putra Mahkota 7/4A, Putra Heights 47650, Subang Jaya, Selangor, Malaysia

 www.estic.com.my

 [estic.my](https://www.instagram.com/estic.my)  [estic.my](https://www.facebook.com/estic.my)